



Inverter SCR for Strobe Flasher Applications 0.8 Amperes/400 Volts



Outline Drawing (Conforms to TO-220)

Dimensions	Inches	Millimeters
A	0.63 Max.	16 Max.
B	0.49 Min.	12.5 Min.
C	0.41 Max.	10.5 Max.
D	0.28	7.0
E	0.18	4.5
F	0.15 Max.	3.8 Max.
G	0.142 ± 0.008 Dia.	3.6 ± 0.2 Dia.

Dimensions	Inches	Millimeters
H	0.125 ± 0.008	3.2 ± 0.2
J	0.99	2.54
K	0.10	2.6
L	0.051	1.3
M	0.051	1.3
N	0.031	0.8
P	0.020	0.5



Description:

The Powerex CR3JM is a glass passivated and molded silicone plastic thyristor for use in automatic strobe flashers.

Features:

- ☐ Large Pulse
- ☐ Glass Passivation
- ☐ Short Turn-off Time
- ☐ Easy Application for Printed Circuits

Applications:

- ☐ Strobe Flasher

Ordering Information:

Example: Select the complete six digit part number you desire from the table - i.e. CR3JM-8 is a 400 Volt, 0.8 Ampere Average SCR.

Type	V _{DRM} /V _{RRM} Volts	Code	Current Rating, I _{T(av)} Amperes (0.8)
CR3JM	400	-8	—

CR3JM
Inverter SCR
for Strobe Flasher Applications
0.8 Amperes/400 Volts

Absolute Maximum Ratings, $T_a = 25^\circ\text{C}$ unless otherwise specified

Ratings	Symbol	CR3JM-8	Units
Repetitive Peak Off-state Voltage	V_{DRM}	400	Volts
Repetitive Peak Reverse Voltage	V_{RRM}	400	Volts
Non-repetitive Peak Off-state Voltage	V_{DJM}	480	Volts
Non-repetitive Peak Reverse Voltage	V_{RSM}	480	Volts
Average On-state Current (Nominal, See Graphs) $T_a = 37^\circ\text{C}$	$I_{\text{T(avg)}}$	0.8	Amperes
Repetitive Peak On-state Current	I_{TRM}	240	Amperes
Peak Gate Power Dissipation	P_{GM}	3	Watts
Average Gate Power Dissipation	$P_{\text{G(avg)}}$	0.3	Watts
Peak Forward Gate Current	I_{FGM}	1	Amperes
Peak Forward Gate Voltage	V_{FGM}	6	Volts
Peak Reverse Gate Voltage	V_{RGM}	6	Volts
Storage Temperature	$T_{\text{(stg)}}$	-40 to 125	$^\circ\text{C}$
Operating Junction Temperature	T_{j}	-40 to 125	$^\circ\text{C}$
Weight	—	2	Grams

Electrical and Thermal Characteristics

Characteristics	Symbol	Test Conditions	Min.	Typ.	Max.
Units					
Voltage Blocking State					
Peak Forward Leakage	I_{DRM}	$T_{\text{j}} = 25^\circ\text{C}$, $V_{\text{DRM}} = \text{Rated}$	—	—	0.1 mA
Peak Reverse Leakage	I_{RRM}	$T_{\text{j}} = 25^\circ\text{C}$, $V_{\text{RRM}} = \text{Rated}$	—	—	0.1 mA
Current – Conducting State					
Peak On-state Voltage	V_{TM}	$T_{\text{c}} = 25^\circ\text{C}$, $I_{\text{TM}} = 3\text{A Peak}$	—	—	1.8 Volts
Gate – Parameters					
Gate Current to Trigger	I_{GT}	$V_{\text{D}} = 6\text{V}$, $R_{\text{L}} = 6\Omega$, $T_{\text{j}} = 25^\circ\text{C}$	—	—	50 mA
Gate Voltage to Trigger	V_{GT}	$V_{\text{D}} = 6\text{V}$, $R_{\text{L}} = 6\Omega$, $T_{\text{j}} = 25^\circ\text{C}$	—	—	2 Volts
Non-triggering Gate Voltage	V_{GD}	$V_{\text{D}} = 1/2 V_{\text{DRM}}$, $T_{\text{j}} = 125^\circ\text{C}$	0.1	—	— Volts
Commutating Capacitor	C_{C}	$C_{\text{M}} = 1800\mu\text{F}$, $V_{\text{CM}} = 350\text{V}$, $I_{\text{TM}} = 240\text{A}$, $L = 50\mu\text{H}$, $V_{\text{GK}} = -6\text{V}$, $T_{\text{a}} = 25^\circ\text{C}$	—	—	2.8 μF


CR3JM

Inverter SCR


for Strobe Flasher Applications

0.8 Amperes/400 Volts


MAXIMUM ON-STATE CHARACTERISTICS




GATE CHARACTERISTICS




COMMUTATING CHARACTERISTICS




COMMUTATING CAPACITOR VS. PEAK ON-STATE CURRENT




COMMUTATING CAPACITOR VS. AMBIENT TEMPERATURE (TYPICAL)




GATE TRIGGER VOLTAGE VS. JUNCTION TEMPERATURE (TYPICAL)



GATE TRIGGER CURRENT VS. GATE CURRENT PULSE WIDTH (TYPICAL)




COMMUTATING CAPACITOR VS. CASE TEMPERATURE (TYPICAL)



CR3JM
Inverter SCR
for Strobe Flasher Applications
 0.8 Amperes/400 Volts

TEST CIRCUIT FOR COMMUTATING CAPACITOR



*3 The circuit between A-B is a substitute for Xenon flash tube.